2025/12/29 03:58

Automated start of workflows with a hotfolder

It is possible to start a workflow or a queue of several workflows from a hotfolder. The configuration has to be defined in the file %FEEDER_RUBY%\config\doc_observer.yml

```
#development:
                                 # environment
hotfolder xy:
  directory watcher:
    directory: /tmp
                                 # directory to watch
    glob: */**
                                 # pattern for files to watch
                                 # interval between runs (in seconds)
    interval: 5.0
                                 # number of runs until a file is stable
    stable: 2
                                # path for persistance file
    persist: /tmp/dw_state.yml
 webservice:
    uri: localhost:3000
                                 # uri for the webservice
    user: user
                                 # user name for basic authentication
                                 # password for basic authentication
    password: passwort123
#Use one of these configuration parameters to define which workflow(s) to
execute
                                 # id of the workflow to execute or...
 workflow id: 3
 workflow ids: [1, 2]
                                 # ...a list of workflow ids to execute
  teardown workflow id: 1
                                # this workflow gets executed when a
worfklow in the list failes (used to clean-up, send message, etc.)
path:
  parent: false
                                 # submit the parent path of the object {
true | false (default) }
  absolute: false
                                 # submit the absolute path of the object {
true | false (default) }
                                 # submit the filename with the extension {
  extension: false
true | false (default) }
```

Configure the service or daemon as followed:

Path to the application: %APPS%\ruby23\bin\bundle.bat

Startup directory: %APPS%\feeder_ruby

Arguments: exec %APPS%\ruby23\bin\ruby lib\doc observer\doc observer.rb hotfolder xy

Where the name of the hotfolder must equal the name defined in doc observer.yml.

From:

https://wiki.docuteam.ch/ - docuteam wiki

Permanent link:

https://wiki.docuteam.ch/doku.php?id=en:docuteam:doc observer&rev=1544689938

Last update: 2019/01/07 11:26

